



TUBING

Size (OD)	Weight/Ft	Wall Thickness	Drift Diameter
3/4" (1.050)	1.2	0.113	0.73
	1.5	0.154	0.648
1" (1.315)	1.8	0.133	0.955
	2.25	0.179	0.848
1-1/4" (1.660)	2.4	0.14	1.286
	3.02	0.191	1.184
	3.24	0.198	1.17
1-1/2" (1.900)	2.9	0.145	1.516
	3.64	0.2	1.406
	4.19	0.219	1.368
2"	3.4	0.165	1.576
2-1/16"	3.25	0.156	1.657
	4.5	0.225	1.519
2-3/8"	4.6 & 4.7	0.19	1.901
	5.3	0.218	1.845
	5.95	0.254	1.773
	6.2	0.261	1.759
	7.7	0.336	1.609
2-7/8"	6.4 & 6.5	0.217	2.347
	7.7 & 7.9	0.276	2.229
	8.6 & 8.7	0.308	2.165
	8.9	0.316	2.149
	9.5	0.34	2.101
	10.4	0.362	2.057
	10.7	0.392	1.997
	11	0.405	1.971
	11.65	0.44	1.901

Size (OD)	Weight/Ft	Wall Thickness	Drift Diameter
3-1/2"	7.7	0.216	2.943
	9.2 & 9.3	0.254	2.867
	10.2 & 10.3	0.289	2.797
	12.8	0.368	2.639
	12.95	0.375	2.625
	15.5	0.449	2.477
	15.8	0.476	2.423
	16.7	0.51	2.355
	17.05	0.53	2.315

4"	9.5	0.226	3.423
	10.8 & 11.0	0.262	3.351
	11.6	0.286	3.303
	13.4	0.33	3.215
	14.8	0.38	3.115
	16.5	0.43	3.015
	19	0.5	2.875
	22.5	0.61	2.655

4-1/2"	10.5	0.224	3.927
	12.6	0.271	3.833
	12.75	0.271	3.833
	13.5	0.29	3.795
	15.5	0.337	3.701
	16.9	0.373	3.629
	17.7	0.402	3.572
	19.2	0.43	3.515
	21.6	0.5	3.375
	24.6	0.56	3.255
	26.5	0.63	3.115

CASING

Size O.D.	Weight/Ft	Wall Thickness	Drift Diameter
4-1/2"	9.5	0.205	3.965
	10.5	0.224	3.927
	11	0.237	3.901
	11.6	0.25	3.875
	12.6	0.271	3.833
	13.5	0.29	3.795
	15.1	0.337	3.701
	16.6	0.373	3.629
	18.8	0.43	3.515

5"	11.5	0.22	4.435
	13	0.253	4.369
	15	0.296	4.283
	18	0.362	4.151
	20.3	0.408	4.059
	20.8	0.422	4.031
	23.2	0.478	3.919
	23.6	0.478	3.919
	24.2	0.5	3.875

5-1/2"	14	0.244	4.887
	15.5	0.275	4.825
	17	0.304	4.767
	20	0.361	4.653
	23	0.415	4.545
	26	0.476	4.423
	28.4	0.53	4.315
	32.3	0.612	4.151
	36.4	0.705	3.965

6-5/8"	20	0.288	5.924
	23.2	0.33	5.845
	24	0.352	5.796
	28	0.417	5.666
	32	0.475	5.55

Size (OD)	Weight/Ft	Wall Thickness	Drift Diameter
7"	17	0.231	6.413
	20	0.272	6.331
	23	0.317	6.241
	26	0.362	6.151
	29	0.408	6.059
	32	0.453	5.969
	35	0.498	5.879
	38	0.54	5.795
	41	0.59	5.695
	44	0.64	5.595
	49.5	0.73	5.415

7-5/8"	26.4	0.328	6.844
	29.7	0.375	6.75
	33.7	0.43	6.64
	39	0.5	6.5
	45.3	0.595	6.31

7-3/4"	46.1	0.595	6.5
--------	------	-------	-----

8-5/8"	24	0.264	7.972
	28	0.304	7.892
	29.35	0.322	7.856
	32	0.352	7.796
	36	0.4	7.7
	40	0.45	7.6
	44	0.5	7.5
	49	0.557	7.386
	52	0.595	7.31

8-3/4"	49.7	0.557	7.5
--------	------	-------	-----

Size (OD)	Weight/Ft	Wall Thickness	Drift Diameter
9-5/8"	32.3	0.312	8.845
	36	0.352	8.765
	40	0.395	8.679
	43.5	0.435	8.599
	47	0.472	8.525
	53.5	0.545	8.379
	58.4	0.595	8.279
	61.1	0.625	8.219

9-3/4"	59.2	0.595	8.404
--------	------	-------	-------

9-7/8"	62.8	0.625	8.469
--------	------	-------	-------

10-3/4"	32.75	0.279	10.036
	40.5	0.35	9.894
	45.5	0.4	9.794
	51	0.45	9.694
	55.5	0.495	9.604
	60.7	0.545	9.504
	65.7	0.595	9.404
	71.1	0.65	9.294

11-3/4"	42	0.333	10.928
	47	0.375	10.844
	54	0.435	10.724
	60	0.489	10.616
	65	0.534	10.526
	71	0.582	10.43

11-7/8"	71.8	0.582	10.555
---------	------	-------	--------

Size (OD)	Weight/Ft	Wall Thickness	Drift Diameter
13-3/8"	48	0.33	12.559
	54.5	0.38	12.459
	61	0.43	12.359
	68	0.48	12.259
	72	0.514	12.191
	77	0.55	12.119
	80.7	0.58	12.059
	85	0.608	12.003
	86	0.625	11.969
	92	0.672	11.875
	98	0.719	11.781

13-1/2"	81.4	0.58	12.184
---------	------	------	--------

13-5/8"	88.2	0.625	12.219
---------	------	-------	--------

14"	92.68	0.65	12.544
	99.43	0.7	12.444
	106.13	0.75	12.344
	112.78	0.8	12.244
	119.38	0.85	12.144

16"	65	0.375	15.062
	75	0.438	14.938
	84	0.495	14.822
	109	0.656	14.5

18-5/8"	87.5	0.435	17.567
---------	------	-------	--------

20"	94	0.438	18.936
	106.5	0.5	18.812
	133	0.635	18.542